	CLASSIFICATIO		2
		AL INTELLIGENCE AGENCY	PEPORT NO.
	INFOR	MATION REPOR	CD NO.
OUNTRY	East Germany		DATE DISTR. 17 April 1953
UBJECT	Radar Training of th Air Division 25X1C	e 1st Volkspolizei	NO. OF PAGES
<u>. </u>	·		NO OF ENCLS.
			SUPPLEMENT TO REPORT NO.
			The order 110.
•		25X1X	
			-dr-dr min - realize distribution distributi
2.	tude and distance of the	redar set is dependent	on the number, type, alti-
	and radar station. The	following data were give	en:
	and radar station. The Altitude of Aircraft	following data were give	en: e of Radar
	and radar station. The Altitude of Aircraft 2,000 meters	following data were give Range	en: e of Radar kilometers
	and radar station. The Altitude of Aircraft 2,000 meters 4,000 meters	following data were give Range 65 100 120	kilometers kilometers kilometers
	and radar station. The Altitude of Aircraft 2,000 meters	following data were give Range 65 100 120	en: e of Radar kilometers kilometers
3.	and radar station. The Altitude of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters	following data were give Range 65 100 120 150 at hes to be cleared from	kilometers kilometers kilometers
3.	and radar station. The Altitude of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters The area of the radar seinterfere with the relaymeters. The average error in meaning the radar seinterfere with the relaymeters.	Range 65 100 120 150 et has to be cleared from (radiation) of the way	kilometers kilometers kilometers kilometers kilometers kilometers
	and radar station. The Altitude of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters The area of the radar seinterfere with the relaymeters. The average error in meaning to measurement is	Range 65 100 120 150 et has to be cleared from (radiation) of the way	kilometers kilometers kilometers kilometers kilometers kilometers m all obstacles which might es, at a radius of 500 to 600 angle of 2 degrees arounts ow 4,000 meters the error in
4.	and radar station. The Altitude of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters The area of the radar seinterfere with the relaymeters. The average error in mean to the radar seinterfere with the relaymeters. The average error in mean to the radar seinterfere with the relaymeters. The average error in mean to the radar seinterfere with the relaymeters.	Range 65 100 120 150 at has to be cleared from (radiation) of the way assurement at an azimuth parings to altitudes helt 300 meters, and to alt	kilometers kilometers kilometers kilometers kilometers mell obstacles which might es, at a radius of 500 to 600 angle of 2 degrees amounts ow 4,000 meters the error in itudes between 4,000 and 8,000
4.	and radar station. The Altitude of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters The area of the radar seinterfere with the relaymeters. The average error in mean ters 700 meters. Taking be measurement is measurement is meters - 500 meters. Technical data: a. Transmitter. Operating frequency	Range Range 65 100 120 150 et has to be cleared from (radiation) of the way assurement at an azimuth parings to altitudes helt and to alt 72.8	kilometers kilometers kilometers kilometers kilometers mall obstacles which might es, at a radius of 500 to 600 angle of 2 degrees amounts ow 4,000 meters the error in itudes between 4,000 and 8,000
4.	and radar station. The Altitude of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters The area of the radar seinterfere with the relaymeters. The average error in mean to the radar seinterfere with the relaymeters. The average error in mean to the radar seinterfere with the relaymeters. The average error in mean to the radar seinterfere with the relaymeters. The average error in mean to the radar seinterfere with the relaymeters. The average error in mean to the radar seinterfere with the relaymeters. The average error in mean to the radar seinterfere with the relaymeters. The average error in mean to the radar seinterfere with the relaymeters.	Range Range 65 100 120 150 At has to be cleared from (radiation) of the way assurement at an azimuth earings to altitudes belt and to alt 72.8 50 in 8-to 40 ki	kilometers kilometers kilometers kilometers kilometers mell obstacles which might es, at a radius of 500 to 600 angle of 2 degrees amounts ow 4,000 meters the error in itudes between 4,000 and 8,000
4.	and radar station. The Altitude of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters The area of the radar seinterfere with the relaymeters. The average error in mest 700 meters. Taking be measurement is 1 meters - 500 meters. Technical data: a. Transmitter. Operating frequency Inpulse frequency Inpulse frequency Inpulse period Average cathode out Feeding capacity	Range Range 65 100 120 150 at has to be cleared from (radiation) of the way assurement at an azimuth earings to altitudes belt and to alt 72.8 50 in 8-to 40 ki 5 ki	kilometers kilometers kilometers kilometers kilometers mall obstacles which might es, at a radius of 500 to 600 angle of 2 dagrees amounts ow 4,000 meters the error in itudes between 4,000 and 8,000 to 73.4 megacycles mpulses per second 10.41 /second .lowatts .lowatts
4.	and radar station. The Altitude of Aircraft 2,000 meters 4,000 meters 6,000 meters 8,000 meters The area of the radar seinterfere with the relaymeters. The average error in mean term of the radar seinterfere with the relaymeters. The average error in mean term of the radar seinterfere with the relaymeters. The average error in mean term of the radar seinterfere with the relaymeters. The average error in mean term of the radar seinterfere with the relaymeters. Technical data: a. Transmitter. Operating frequency In pulse frequency In pulse period Average cathode out	Range Range 65 100 120 150 at has to be cleared from (radiation) of the way assurement at an azimuth earings to altitudes belt and to alt 72.8 50 in 8-to 40 ki 5 ki	kilometers kilometers kilometers kilometers kilometers mall obstacles which might es, at a radius of 500 to 600 angle of 2 degrees amounts ow 4,000 meters the error in itudes between 4,000 and 8,000 to 73.4 megacycles mpulses per second 10.41 /second .lowatts

S	ECRET/	25X1	25X1A
b.	Receiver.		
	Frequency range first interrediate frequency second interrediate frequency	110 to 160 kilocycles 5.95 to 6.05 megacycles 1.65 to 1.75 megacycles	
Ca	Power supply		
	Alternating current	50 cycles, 220 volts	

- 6. Operation. During summer months, four hours are required to erect the radar set, and during the winter months, six hours are required for the procedure. The set is ready for operation 3 to 5 minutes after it has been turned on. The starting tire of the generator is three minutes in summer and 5 to 8 minutes in winter. Fuel consumption of the generator: 335 gramms gasoline and 17 gramms cil per hp per hour. After six hours of continuous operation, a second generator has to be turned on.
- 1. Comment. It is believed that the data given refer to the approximate figures of the Fumbo or SCR-602 radar sets. The average error in measurement is probably to high, while the frequency range of the receiver is believed to be too small. The training was performed in connection with early warning stations.

25X1A

SECRET/ 25X1